ADAM-5052 ADAM-5053S ADAM-5055S

8-ch Isolated Digital Input Module

32-ch Isolated Digital Input Module

16-ch Isolated Digital I/O Module with LED







Self-service Terminals

Specifications

General

Certifications

Connectors 1 x Plug-in screw terminal

(# 14 ~ 22 AWG)

Enclosure ABS+PC Power Consumption 0.27 W (max.)

Digital Input

Channels 8

 Input Resistance 3 kΩ/0.5 W

 Logic Level Logic level 0: 1 V_{max}

Logic level 1: 3.5 ~ 30 V

Protection

 Isolation Voltage $5000 \, V_{RMS}$

Ordering Information

ADAM-5052

8-ch Isolated Digital Input Module

Specifications

General

Certifications CE, FCC class A Connector 40 pin ABS+PC Enclosure Power Consumption 1 W (max.)

Digital Input

32 Channels Channel I/O Type

24 Vdc (Sink/Source)

Logic Level

 Wet Contact Logic level 0: 10 V Max. Logic level 1: 19 ~ 35 V

Protection

 Isolation Voltage 2.500 Vpc Overvoltage $35 V_{DC}$ Protection

Note: only for ADAM-5550 Series

Ordering Information

ADAM-5053S

ADAM-3920

32-ch Digital Input Module 20-pin Flat Cable Wiring

PCL-10220

Board

40-pin IDC to two 20-pin IDC cable, 1 m

Specifications

General

Certifications

Connectors 1 x Plug-in screw terminal

(# 14 ~ 28 AWG)

ABS+PC Enclosure

 LED Indicators On: Active Off: Inactive

• Power Consumption 0.68 W (max.)

Digital I/O

Channels 16

 Channel I/O Type 8 DO, 8 DI

 Digital Input Dry contact:

> Logic level 0: open Logic level 1: close to GND

Wet contact:

Logic level 0: 3 V max.

Logic level 1: 10 ~ 50 V Open collector to 40 V Digital Output

200 mA max. load Power Dissipation Channel: 1 W max.

> Total: 2.2 W (8 channels)

Protection

 Isolation Voltage 2,500 V_{DC} Overvoltage

70 V_{DC} (DI only)

Ordering Information

ADAM-5055S

Protection

16-ch Isolated Digital I/O Module with LED